CMG Tech-X 100Cr6 Steel Filament





Page 1 of 7 Revision: 16 April 2024 Version number: 1.0

SECTION 1: Identification of the substance/mixture and company/undertaking

1.1 Product identifier CMG Tech-X 100Cr6 Steel Filament

1.2 Relevant identified uses of the substance or mixture and uses advised against

Metal filament for 3D printing fabrication. Uses advised against: not available.

1.3 Details of the supplier of the safety data sheet

CMG Technologies Ltd, Building I1, Thompson Drive,

Base Business Park,

Rendlesham IP12 2TZ,

United Kingdom.

Tel: +44 (0) 1394 445 100; email: obatka@cmgtechnologies.co.uk;

www.cmgtechnologies.co.uk

1.4 Emergency telephone number

Tel +44 (0) 1394 445 100 (UK business hours).

UK: 111 (public NHS number for less urgent medical problems). Medical professionals can contact the National Poisons Information Service

(NPIS): 0344 892 0111.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to CLP Regulation (1272/2008)

This product does not meet the criteria for classification in any hazard class according to Regulation (EC) No. 1272/2008, or GB equivalent, and it is not mandatory to supply a safety data sheet, but this document provides information and advice concerning safe handling of the product.

2.2 Label elements

Pictograms None.

Signal word None.

Hazard statements None.

Precautionary statements None.

Supplemental information

Not available.

2.3 Other hazards The product does not contain any ingredient identified as having

endocrine disrupting properties.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

	Declarable components	EC No.	CAS No.	Classification, supplemental hazards, ATE, M-factor, and SCL
١	None.			







Page 2 of 7 Revision: 16 April 2024 Version number: 1.0

Other compo	Other components							
Chromium	0.5-10	231-157- 5	7440-47- 3	01-2119485652- 31-0219	Not classified			

SECTION 4: First aid measures

4.1 Description of first aid measures

Inhalation For symptoms of inhalation, eg coughing, breathing difficulty, or

> respiratory irritation, remove exposed person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical help if

symptoms persist.

Skin For skin contamination, remove contaminated clothing and wash affected

area with soap and water. If irritation, rash, or other symptom occurs, get

medical help. Wash contaminated clothing before re-use.

If product or dust or vapour cause irritation, irrigate affected eye with Eye

room-temperature water or eyewash solution for several minutes, occasionally lifting eyelids. Remove any contact lenses if easy to do.

Continue rinsing. Get medical help if irritation persists.

If in mouth, rinse mouth thoroughly with water and spit out rinsings. Water Ingestion

> may be given to drink if product has been swallowed. If patient feels unwell or is concerned, get medical help. Do not induce vomiting, unless

instructed by medical personnel.

4.2 Most important symptoms and effects,

both acute and delayed

Not available.

of 4.3 Indication any immediate medical attention and special

treatment needed

Treat symptoms as they occur.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable In case of fire, use extinguishing powder, sand, or water spray.

Unsuitable Not available.

5.2 Special hazards arising from the substance or

mixture

The product is not classified as flammable, but will decompose if involved in a fire, producing smoke, and hazardous fumes and gases.

5.3 Advice for firefighters Remove containers from fire or cool them with water spray. For larger

fires, firefighters should wear breathing apparatus and protective clothing.

CMG Tech-X 100Cr6 Steel Filament





Page 3 of 7 Revision: 16 April 2024 Version number: 1.0

Section 6: Accidental release measures

6.1 Personal precautions, protective equipment

emergency and

procedures

The product is supplied in small containers as coiled filament on a roll, which can be collected.

In a professional setting, wear personal protection.

Ventilate area. Avoid creating airborne dust. Follow prescribed

procedures for responding to spills.

6.2 Environmental precautions

Prevent product from entering water courses or drainage system.

6.3 Methods and material for containment and

cleaning up

Clean up spill as soon as possible.

For small quantities, collect pieces, and wash off any residue with

detergent and water.

For large quantities, carefully sweep up, preventing formation of airborne

dust, or collect using vacuum cleaner equipped with air filtration.

Collect spill, contaminated materials, and washings in a container for disposal.

6.4 Reference to other

sections

For recommended personal protective equipment, see Section 8.

For disposal considerations, see Section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid skin and eye contact with the product, and inhalation of vapours or dust. Use only in a well-ventilated area. See Section 8 for engineering

controls and personal protection.

Wash hands after use. Do not eat, drink or smoke when using this

product.

Upon mechanical (eg cutting, grinding or polishing), thermal, or chemical treatment the product can release hazardous dust. Do no inhale dusts when formed. Avoid generating airborne dust and keep work areas clean Dust in sufficient concentration can result in an explosive mixture in air.

Eliminate open flame and other sources of ignition.

7.2 Conditions for safe storage, including any incompatibilities

Keep packages in a cool, dry place away from direct sunlight. Keep out of reach of children.

7.3 Specific end use(s)

Metal filament for 3D printing fabrication.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

EU limit values None. UK: National limit values

Chromium: WELs: long-term exposure limit (8 h TWA) 0.5 mg/m³.

BS EN 14042:2003; Workplace Atmospheres; Guide for the Application Monitoring procedure

and Use of Procedures for the Assessment of Exposure to Chemical and

Biological Agents, or specific national equivalent.

CMG Tech-X 100Cr6 Steel Filament





Page 4 of 7 Revision: 16 April 2024 Version number: 1.0

Other: human health (DNELs, DMELs)

Chromium: DNELs: workers, long-term exposure, local effects, inhalation,

 0.5 mg/m^3 .

environmental Other: (PNEC)

Chromium: PNECs: freshwater, 0.0065 mg/L; freshwater sediment, 206 mg/kg dry sediment; soil, 21.1 mg/kg dry soil; oral, 0.12 mg/kg food.

8.2 Exposure controls

Engineering controls Use in a well-ventilated area (3 to 5 air changes/hour) is recommended.

For bulk use, and for processing causing formation of dust or fumes, local

exhaust ventilation is recommended.

Personal protective equipment

The need for personal protective equipment should be based on a

workplace risk assessment for the particular use.

Avoid skin and eye contact by wearing chemical resistant gloves (eg EN374, EN 420; nitrile rubber gloves, 0.2 mm) and eye protection (EN166). Where more extensive contact may occur, wear protective

clothing (eg apron, overalls).

Additional protection from burns may be required for hot processing. A dust mask (EN 143) may be required if the processing causes dust. For guidance on respiratory protection see HSE Guide HSG53 and BS4275. PPE should conform to British (EN) standards, or national equivalent.

Consult PPE manufacturers concerning breakthrough times.

Environmental exposure

controls

Not available.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

(a) Physical state Coiled filament on a roll

(b) Colour Grey or dark grey

Odourless (c) Odour

(d) Melting/freezing point 120 to 160 °C

Boiling point or initial boiling point and boiling

Not available

range

Flammability Not classified as flammable

(a) Lower and upper

explosion limit

Not available

(h) Flash point Not available Not available Auto-ignition temp. Decomposition temp. Not available (k) pH Not available

Not applicable to solid Kinematic viscosity (m) Solubility Not soluble in water

CMG Tech-X 100Cr6 Steel Filament





Page 5 of 7 Revision: 16 April 2024 Version number: 1.0

(n) Partition coeff. n- Not available

octanol/water (log value)

(o) Vapour pressure Not available

(n) Density annual density Matel assuments

(p) Density or rel. density Metal components: 7.8

(q) Relative vapour density Not available

(r) Particle characteristics Filament of 1.75 or 2.85 mm diameter

9.2 Other information No ingredient classified as explosive or oxidising.

SECTION 10: Stability and reactivity

10.1 Reactivity Not available.

10.2 Chemical stability Stable.

10.3 Possibility of Not available

hazardous reactions

10.4 Conditions to avoid Open flames, strong heat

10.5 Incompatible materials Strong oxidizing agents (eg hydrogen peroxide), strong acids, alkalis.

10.6 Hazardous decomposition

products

Not available.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

(a) Acute toxicity Based on available data on the ingredients, the classification criteria are

not met for the oral, dermal or inhalation routes of exposure.

ATE_{mix} (oral) > 2000 mg/kg; ATE_{mix} (dermal) > 2000 mg/kg; ATE_{mix}

(inhalation, mist) > 5 mg/L.

(b) Skin corrosion/irritation Based on available data on the ingredients, the classification criteria are

not met.

(c) Serious eye Based on available data on the ingredients, the classification criteria are

not met.

(d) Respiratory or skin

damage/irritation

sensitisation

Based on available data on the ingredients, the classification criteria are

not mot

No relevant ingredient has been classified for this effect.

(e) Germ cell mutagenicity Based on available data on the ingredients, the classification criteria are

not met

No relevant ingredient has been classified for this effect.

(f) Carcinogenicity Based on available data on the ingredients, the classification criteria are

not met.

No relevant ingredient has been classified for this effect.

(g) Reproductive toxicity Based on available data on the ingredients, the classification criteria are

not met.

CMG Tech-X 100Cr6 Steel Filament





Page 6 of 7	Revision: 16 April 2024	Version number: 1.0
-------------	-------------------------	---------------------

No relevant ingredient has been classified for this effect. (h) STOT-single exposure Based on available data on the ingredients, the classification criteria are not met. No relevant ingredient has been classified for this effect. STOT-repeated Based on available data on the ingredients, the classification criteria are (i) exposure not met. No relevant ingredient has been classified for this effect. Aspiration hazard Based on available data on the ingredients, the classification criteria are

not met.

11.2 Information on other No ingredient has been classified with endocrine disrupting properties

relevant for humans.

SECTION 12: Ecological information

hazards

12.1 Toxicity Based on available data on the ingredients, the classification criteria are

not met.

No relevant ingredient has been classified for this effect.

12.2 Persistence and Product comprises of metal powders in a polymer, and is expected to

degradability persist in the environment.

12.3 Bioaccumulative Bioaccumulation not applicable to metals. potential

12.4 Mobility in soil Not available.

12.5 Results of PBT and PBT or vPvB assessment not applicable to metals. vPvB assessment

12.6 Endocrine disrupting No ingredient has been classified with endocrine disrupting properties properties relevant for the environment.

12.7 Other adverse effects The mixture is not classified as hazardous to the ozone layer.

SECTION 13: Disposal considerations

13.1 Waste treatment Product comprises metal powders in a polymer. Recycling is methods recommended for bulk disposal of this product. Landfill or disposal via the

drains is not recommended.

Disposal must be in accordance with national and local regulations. Chemical residues generally count as special waste. General EU

requirements are given in Directive 2008/98/EC.

SECTION 14: Transport information

14.1 UN Number Not classified as dangerous goods for transport.

14.2 UN proper shipping Not applicable. name

14.3 Transport hazard Not applicable.

class(es)

CMG Tech-X 100Cr6 Steel Filament





Page 7 of 7 Revision: 16 April 2024 Version number: 1.0

14.4 Packing group Not applicable.

14.5 Environmental hazards Not classified as marine pollutant/environmentally hazardous.

14.6 Special precautions for

user

Not available.

14.7 Maritime transport in bulk according to IMO

instruments

Not applicable. This product is not intended to be transported by sea in

bulk containers.

SECTION 15: Regulatory information

15.1 Safety, health and

environmental
regulations/legislation
specific for the
substance or mixture

UK: Control of Substances Hazardous to Health Regulations 2002

(COSHH), as amended.

COSHH Essentials: Easy Steps to Control Chemicals; HSE Books 2003

(also available on the HSE web site).

Workplace Exposure Limits EH40/2005 (Fourth Edition, 2020); Health

and Safety Executive.

15.2 Chemical safety assessment

Not available.

SECTION 16: Other information

Revisions This SDS is the first version in EU format (Regulation 2020/878), using

classification according to the CLP Regulation (1272/2008).

Abbreviations ATE, acute toxicity estimate; DNEL, derived no-effect level; DMEL,

derived minimum effect level; PBT, persistent, bioaccumulative, and toxic; PNEC, predicted no-effect concentration; SCL, specific concentration limit; STOT RE, specific target organ toxicity repeated exposure; STOT SE, specific target organ toxicity single exposure; TWA, time-weighted average; vPvB, very persistent, very bioaccumulative;

WEL, UK workplace exposure limit.

References Search for chemicals; available at the European Chemicals Agency

website: http://echa.europa.eu/.

Basis of classification The mixture is self-classified from available information on the

ingredients.

List of hazard statements None.